

CAS~H264CKE



- ◇8-Channel H.264 Network Digital Video Recorder (4-channel with D1)
- ◇Video Compression: H.264; Video System: PAL/NTSC
- ◇Video input/output: BNC 4-channel Input and 1-channel BNC Output and 1-channel VGA Output; VGA Resolution: 1024x768,1280x1024
- ◇Audio input/output: RCA 2-channel input/ RCA 1-channel output
- ◇Alarm input/output: 2-channel input/1-channel output
- ◇Display resolution: D1 704 x 576 (PAL); D1 720 x 480 (NTSC)
- ◇Display frame rate: 100fps(PAL);120fps (NTSC) (shared by 4 cameras)
- ◇Recording resolution: D1 704×576 /CIF 352×288 (PAL); D1 704×480 /CIF 352×240 (NTSC)
- ◇Recording frame rate: D1@100fps/CIF@100fps(PAL); D1@120fps/CIF@120fps(NTSC)
- ◇Playback resolution: 4 x D1/CIF
- ◇RJ-45 Ethernet connector; Support Static, Dynamic IP and Support TCP/IP, PPPOE, DHCP, DNS DDNS, SNTP, NTP, UPNP
- ◇ Support Internet Explorer, Mobile phone and special client software
- ◇With RS485 x 1, 2 × USB, 1 × IR Controller , 1 × USB2.0 mouse
- ◇Support PELCO-P&PELCO-D PTZ control
- ◇Support 1 SATA Hard Disk interface (2TB in total) ◇Multi-language OSD
- ◇Dimension: 320x273x55mm (LxWxH) Weight:3.5Kg

*3414 North Shadeland Avenue
Indianapolis, Indiana 46226
(317) 862-0622*

www.cascctv.com

Cornerstone Alarm & Security, Inc.

Compression Standard	H.264 (ASIC)
Resolution	BNC 8-channel Input and 1-channel BNC Output and 1-channel VGA Output; VGA Resolution: 1024x768,1280x1024
Hard Disk	1 SATA Hard Disk interface(Support Capacity from 40G to 4T in Total)
Video Signal	PAL (625Line, 50f/s) , NTSC (525Line, 60f/s)
Video Input	8 channel, BNC , 1.0V p-p/75Ω
Composite Video Output	1 channel, BNC, 1.0V p-p/75Ω
Monitor Video Output	1 channel, BNC, 1.0V p-p/75Ω
VGA Interface	1 VGA,Resolution:800x600/60HZ,1024x768/60HZ
Audio Input	2 channel, RCA
Audio Output	1 channel, RCA
Alarm Input	2 Channel, Trigger closed without Voltage, Open or Closed
Alarm Output	1 Channel, Trigger closed without Voltage, Open or Closed
Alarm Mode	Sensor Input, Motion Detection, Video Loss, Full Disk Space.
Network	Ethernet (10/100M), LAN、 WAN and ADSL
Control Way	USB2.0 Mouse, Remote Control, Camera, RS485 x 1
Password	Encrypted by 128-bit Numerical Digits with 2-Level Password Protection
Power Supply	DC12V 3.0A
Consumption	10W (Without HDD)
Working Environment	Temperature: +5°C~+50°C ; Humid : < 90%
Device Dimension	320x273x55mm
Weight	3.5kgs

*3414 North Shadeland Avenue
Indianapolis, Indiana 46226
(317) 862-0622*

www.cascctv.com