

CASH264V



4, 8, or 16 channel DVR

Features:

- *Stand-Alone DVR,H.264 Compression
- *High quality video Display : NTSC (720x480), PAL (704x576) real time display
- *Multiple Recording/ Search Categories:Date/Time, Event, Manual, Schedule, alarm, motion detection
- *Real time recording support: 240 Fps for NTSC at CIF image (200 Fps for PAL)
30 Fps for NTSC at D1 image (25 Fps for PAL)
- *4, 8 or 16 ch Video recording at the same time
- *Pentaplex: Live, Record, Playback, Back-up and Network at the same time
- *Backup: CD-RW (Option: DVD-RW), USB 2.0 and NET backup supported
- *PTZ camera control in local and remote area
- *E-mail notification
- *3G support
- *With multi-languages menu

Network Viewer:

- *Static, Dynamic IP and DDNS , Support Internet Explorer and special client software
- *Remote Live Monitoring, file searching, Backup, Playback and PTZ camera control
- *Remote Configuration, Firmware Upgrade and Event (Alarm, Motion) Notification
- *Full duplex two way audio transmission

*3414 North Shadeland Avenue
Indianapolis, Indiana 46226
(317) 862-0622*

www.cascctv.com

Cornerstone Alarm & Security, Inc.

Compression Standard	H.264 (ASIC)
Video System	NTSC / PAL
Video Input/Output	BNC 8CH In/1CH BNC Out/ 1CH VGA Out
Audio Input/Output	RCA 1CH In/ 1CH Out
Alarm Input/Output	Alarm 2CH In/ 1CH Out
Preview resolution	720 x 480 (NTSC), 704 x 576 (PAL) ; Playback resolution : 4x CIF
Maximum Recording Rate(CIF/D1)	CIF:352×240 with 480 Fps (NTSC); 352×288 with 400 Fps (PAL) D1:720×480 with 30 Fps (NTSC); 704×576 with 25 Fps (PAL)
Image Quality Setting	Supper Best, Well, Good, Medium, Normal and Bad
Hard Disk Storage	Support 1 SATA HDD, unlimited for the capacity
Multiplex Operation	Live display/ record/ playback/ backup/ network transmit
Recording Mode	Manual/ Timer/ Motion
Playback Mode	Multiple slow and rapid play speeds, manual and single-frame play modes, and support of drag the sliding bar to set
Backup Device	USB flash disk / Network
Pre-alarm Recording	Recording for 10 seconds before alarming
Network Protocol	TCP/IP、PPPOE 、 DDNS and NTP
Ethernet remote view	Support remote surveillance up to 10 users simultaneously
Mobile phone View	YES
VGA Interface	VGA output
Video Adjustable	Hue /Saturation /Contrast /Brightness adjust
PTZ Control	YES, built-in RS-485 port
USB Mouse	YES
Power Source	DC 12V 3A
Dimension	250(W) x 45(H) x 224(D)

*3414 North Shadeland Avenue
Indianapolis, Indiana 46226
(317) 862-0622*

www.cascctv.com

Cornerstone Alarm & Security, Inc.

*3414 North Shadeland Avenue
Indianapolis, Indiana 46226
(317) 862-0622*

www.cascctv.com